S D FIRE PROTECTION

All Types of Fire Fighting Solutions













Regd. Office Add.: D-3/260, Main Circular Road, 3rd Pusta, Sonia Vihar, North East Delhi-110094
E-Mail Id: dkm@sdfireprotection.in | **Website:** sdfireprotection.in | **Contact:** 9319890651, 9999772110

ABOUT US

SD Fire Protection is the prime supplier, authorised dealer / distributor of the most popular fire fighting equipment brands. We have expertise in the field of fire fighting laying and we have taken our expertise and experience into the Indian market to establish a reputation for excellence and customer support.

We have never left working with best companies in their field to reduce the fire risk to minium in living spaces and industrial areas. All the goods and services we offer to our clients certified by internationally recognised certification bodies.

SD Fire Protection is the prime service provider in the field of fire fighting. We Provide the complete products/assoseries, like Fire Extinguishers, Hydrant, Valves, Hose Reel Drum, Fire Hose Box, Fire Bridge Inlet, Sprinkler, Manual Call Point, Fire Hooter, Alarm Panel, etc. All our products are ISI certified that ensures complete safety against fire. We also work as turnkey basis and provide complete solution in the field of firefighting. We strive for the excellence and make sure that the all our customers receive a high quality product and service with minimal disruption. We provide a potent solution to the various customers in Industrial, Residential and Commercial establishments such as Malls, Hospitals, Schools and other buildings, etc. Right from design, selection off equipment to the installation and commissioning, the entire process is done by our expert team.

We are here to serve you the best!

VISION

We believe in serving the best and our prime purpose is to save precious life and property by providing top class quality products & implementing advance safety and protection system. So we deliver the best possible Quality and Services within our customer's budget and schedule.

MISSION

To be customers first choice provider of fire fighting solution, offering a varied, effective and unique set of products and services, We aim for saving lives and protection property at all times.

PRODUCT RANGE



Single Head Hydrant Valve

Material	:	Stainless Steel (304 & 202), Gun Metal & C.I.
Size	:	As per IS 5290 : 1993
PCD	:	145mm & 160mm
Pressure	:	21 Kgf/cm^2



Double Head Hydrant Valve

Material	:	Stainless Steel (304 & 202), Gun Metal & C.I.
Size	:	As per IS 5290 : 1993
PCD	:	145mm & 145mm
Pressure	:	21 Kgf/cm^2



Fire Hose Delivery Coupling

Material	:	Stainless Steel (304 & 202), Gun Metal & Aluminium
Size	:	As per IS 903 : 1993
PCD	:	63mm
Pressure	:	21 Kgf/cm^2



Branch Pipe & Nozzle Set

Material	:	Stainless Steel (304 & 202), Gun Metal & Aluminium
Size	:	As per IS 903 : 1993
PCD	:	163mm & 145mm
Pressure	:	21 Kgf/cm^2



Fire Bridge Two Way Inlet

Material	:	C.I. Body & Gun Metal/ Stainless Steel (S.S.04/202) Parts, Fitted with Spring Loaded NRV and Rubber Cap with Chain.
Inlet	:	100mm NB Flanged Inlet.
Flange Size	:	PCD-180mm, OD-220mm, ID-100mm No. of hole : 08 Nos, Dia of hole-19mm.



Fire Bridge Three Way Inlet

Material	:	C.I. Body & Gun Metal/ Stainless Steel (S.S.04/202) Parts, Fitted with Spring Loaded NRV and Rubber Cap with Chain.
Inlet	:	100mm NB Flanged Inlet.
Flange Size	:	PCD-240mm, OD-285mm, ID-144mm No. of hole : 08 Nos, Dia of hole-23mm.



Fire Bridge Four Way Inlet

Material	:	C.I. Body & Gun Metal/ Stainless Steel (S.S.04/202) Parts, Fitted with Spring Loaded NRV and Rubber Cap with Chain.
Inlet	:	100mm NB Flanged Inlet.
Flange Size	:	PCD-240mm, OD-285mm, ID-144mm No. of hole : 08 Nos, Dia of hole-23mm.



Fire RRL Hose Pipe

Material	:	Rubber and Canvas
Standard Length	:	15 mtr. & 30 mtr. (As per IS 636-Type: A & B)
End Connection	:	As per Customer Requirement
Diameter	:	63mm



Fire Hose Reel Drum

Material	:	M.S. Sheet & Aluminium
Size	:	As per IS 884 : 1985
Hydrostatic Test	:	21 Kgf/cm2
Type	:	Manual Type / Swing Movement



Thermoplastic Hose Pipe Type I & II

Hydrostatic Test	:	21 Kgf/cm2
Discharge	:	24 LPM
Range	:	6 mtrs. (Min.)



Fire Extinguisher

Type	:	ABC, Co2, FOAM, WATER Co2, DCP
Capacity	:	1 Kg, 2 Kg, 4 Kg, 6 Kg, IS Specification9 Kg, 50 Kg
Hydrostatic Test	:	35 Kgf/cm^2 Pressure
Operating Valve	:	Squeeze Grip Type with Discharge Hose & Nozzle



Adapter

Material	:	Stainless Steel (304 & 202), Gun Metal or Aluminum
Size	:	As per Indian Standard Specification



Sprinkler



Double Door Hose Box



Single Door Hose Box



Fire Bucket



Shut Off Nozzle



Butter Fly Valve



Ball Valve



Fire Hooter



Smoke Detector



Fire Alarm Panel



Fire Monoblock Pump



Fire Ball